

Bath fluid Thermal C20S

JULABO Thermal bath fluids are ideally suited for all of your temperature control applications and guarantee safe and reliable operation. Choosing the proper bath fluid is critical for best results in temperature control. Viscosity, oxidation characteristics and heat transfer of Thermal fluids are specifically matched with each JULABO temperature control unit.

JULABO Thermal bath fluids have been carefully selected and are optimized for maximum performance with JULABO instruments.

Benefits

- Low toxicity
- Low viscosity
- High stability
- Minimum odor
- Good heat conductivity
- Low corrosion tendency
- Wide temperature ranges



Technical Data

Order no. 5 liters	8891409
Order no. 10 liters	8891408
Working temperature (°C)	0...+220
Flash point (°C)	> +232
Fire point (°C)	> +476
Viscosity (kinematic at 20 °C in mm²/s)	20
Density (at 20 °C in g/cm³)	0.97
Pour point (°C)	-60
Boiling point (°C)	>250
Ignition temperature (°C)	>476
Color	light brown

JULABO Contact

JULABO USA Inc.
884 Marcon Boulevard, Allentown, PA 18109
Phone: 610-231-0250
Phone: 800-458-5226 (Toll-Free)

info.us@julabo.com

JULABO Services

Product finder, Accessory search, 1 PLUS Warranty,
Catalog download, Callback service, Operating manuals,
Safety data sheets, Software and more

www.julabo.com