

Bath fluid Thermal H350

JULABO Thermal bath fluids are ideally suited for all of your temperature control applications and guarantee safe and reliable operation. Choosing the proper bath fluid is critical for best results in temperature control. Viscosity, oxidation characteristics and heat transfer of Thermal fluids are specifically matched with each JULABO temperature control unit.

JULABO Thermal bath fluids have been carefully selected and are optimized for maximum performance with JULABO instruments.

Benefits

- Low toxicity
- Low viscosity
- High stability
- Minimum odor
- Good heat conductivity
- Low corrosion tendency
- Wide temperature ranges



Technical Data

Order no. 5 liters	8940111
Working temperature (°C)	+50...+350
Flash point (°C)	210
Fire point (°C)	235
Viscosity (kinematic at 20 °C in mm²/s)	47.1
Density (at 20 °C in g/cm³)	1.04
Pour point (°C)	<-34
Boiling point (°C)	390
Ignition temperature (°C)	450
Color	light brown

JULABO Contact

JULABO USA Inc.
884 Marcon Boulevard, Allentown, PA 18109
Phone: 610-231-0250
Phone: 800-458-5226 (Toll-Free)

info.us@julabo.com

JULABO Services

Product finder, Accessory search, 1 PLUS Warranty,
Catalog download, Callback service, Operating manuals,
Safety data sheets, Software and more

www.julabo.com