

Bath fluid Thermal P60

JULABO Thermal bath fluids are ideally suited for all of your temperature control applications and guarantee safe and reliable operation. Choosing the proper bath fluid is critical for best results in temperature control. Viscosity, oxidation characteristics and heat transfer of Thermal fluids are specifically matched with each JULABO temperature control unit.

JULABO Thermal bath fluids have been carefully selected and are optimized for maximum performance with JULABO instruments.

Benefits

- Low toxicity
- Low viscosity
- High stability
- Minimum odor
- Good heat conductivity
- Low corrosion tendency
- Wide temperature ranges



Technical Data

Order no. 5 liters	8891413
Order no. 10 liters	8891412
Working temperature (°C)	-60...+250
Flash point (°C)	+130
Fire point (°C)	+148
Viscosity (kinematic at 20 °C in mm²/s)	5
Density (at 20 °C in g/cm³)	0.918
Pour point (°C)	-65
Boiling point (°C)	>205
Ignition temperature (°C)	350
Color	clear

JULABO Contact

JULABO USA Inc.
884 Marcon Boulevard, Allentown, PA 18109
Phone: 610-231-0250
Phone: 800-458-5226 (Toll-Free)

info.us@julabo.com

JULABO Services

Product finder, Accessory search, 1 PLUS Warranty,
Catalog download, Callback service, Operating manuals,
Safety data sheets, Software and more

www.julabo.com